

SPECIFICATIONS

Page 1 of 2
FR0932344

ITEM NO.	DESCRIPTION	CHECK IF AS SPECIFIED	DESCRIBE FULLY IF NOT AS SPECIFIED
1	CARRIER -PURON Duct-Free Split-System Condensing Unit 38HDR036-5 DFS 36K CDU R410A		
	38HDR (OUTDOOR UNIT)		
	13 SEER		
	18,000 – 60,000 BTUH		
	ELECTRIC HEAT AND AUTO CHARGEON OVER ON HEAT PUMP		
	ELECTRO-MECHANICAL CONTROL ALLOWS ULTIMATE FLEXIBILITY		
	AUTO SWEEP STANDARD		
	SLIDE-IN AIR FILTER		
	RESTART FUNCTION AFTER POWER FAILURE – THERMOSTAT DEPENDENT		
	FRESH AIR INTAKE MIN. 30%		
	INCLUDES MOUNTING BRACKETS		
	MIN WARRANTY: 1 YEAR PARTS AND 5 YEARS ON THE COMPRESSOR		
	MOTORIZED LOUVERS		
	SELECTABLE FAN SPEEDS		
	SYSTEM VOLTAGE: OUTDOOR: 230 V. 3 PH		
	CONTROL REMOTE-WIRED WIDTH: 44 9/16 INCH HEIGHT: 37 3/16 INCH DEPTH: 17-1/16 INCH WEIGHT MAXIMUM: 260 LBS		
	REFRIGERANT LINES: LIQUID LINE 3/8 INCH VAPOR LINE 3/4 INCH		
2	CARRIER - PURON UNDER CEILING INDOOR UNIT 40QAC036-3		
	3 TON		
	AC- R410A		

SPECIFICATIONS

Page 2 of 2
FR0932344

	WIDTH: 58-13/16 IN HEIGHT 9-15/16 INCH DEPTH: 23-1/8 INCH WEIGHT: MAX 120 LBS		
	MOUNTING BRACKETS INCLUDED		
	MIN WARRANTY: 1 YEAR PARTS AND 5 YEARS ON THE COMPRESSOR		
	Seer – 13		
	MOISTURE REMOVAL (pints per hr.) 6		
	Air flow: (low 640- med- 740 High- 840		
	Sound Power: Low – 62.97 Med – 66 High – 68.4		
	Sound Pressure: Low – 51.9 Med – 55 High – 57.4		
	Controls Remote: wired Voltage 24 v		
	Low ambient operation down to -20 degrees F.		
	MOCP: Indoor: 15 Outdoor:		
3	CARRIER - KAAWS0101 AAA WINTER START CONTROL TO GO ALONG WITH THE ABOVE UNITS		
4	CARRIER -CONDENSATE PUMP 53DS-900-081 TO GO ALONG WITH THE ABOVE UNITS		
5	CARRIER - LOW AMBIENT CONTROL 53DS-900-086 TO GO ALONG WITH THE ABOVE UNITS		